






TECHNICAL PARAMETERS

Capacity	Type	Colour	Rated Working Load				Width In Safety factor	
			Vertical	Basket	Chocket	Angle 45°	5.1	7.1
								
			Tonnes	Tonnes	Tonnes	Tonnes	mm	mm
			1	Flat		1	2	0.8
1	Round		1	2	0.8	1.4		
2	Flat		2	4	1.6	2.8	50	60
2	Round		2	4	1.6	2.8		
3	Flat		3	6	2.4	4.2	75	90
3	Round		3	6	2.4	4.2		
4	Flat		4	8	3.2	5.6	100	120
4	Round		4	8	3.2	5.6		
5	Flat		5	10	4	7	125	150
5	Round		5	10	4	7		
6	Flat		6	12	4.8	8.4	150	180
6	Round		6	12	4.8	8.4		
8	Flat		8	16	6.4	11.2	200	240
8	Round		8	16	6.4	11.2		
10	Flat		10	20	8	14	250	300
10	Round		10	20	8	14		
12	Flat		12	24	9.6	16.8	300	300
12	Round		12	24	9.6	16.8		
16	Flat		16	32	12.8	22.4	200	325
16	Round		16	32	12.8	22.4		
20	Flat		20	40	16	28	250	350
20	Round		20	40	16	28		

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserves the right to modify design, dimensional parameters, component and composition of material without prior notice

