

TECHNICAL PARAMETERS

| Product Code | KT005103 | KT010103 | KT015103 | KT020103 | KT020203 | KT030203 | KT050203 | KT075303 | KT100403 | KT150603 | KT200803 |
|--------------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Capacity (Tonnes) | 0.5 | 1 | 1.5 | 2(1) | 2(2) | 3 | 5 | 7.5 | 10 | 15 | 20 |
| Standard lift (Mtr) | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| Number of falls | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 3 | 4 | 6 | 8 |
| Load chain dia (mm) | 6 | 6 | 8 | 8 | 6 | 8 | 10 | 10 | 10 | 10 | 10 |
| Test load (Tonnes) | 0.75 | 1.5 | 2.25 | 3 | 3 | 4.5 | 7.5 | 11.25 | 15 | 22.5 | 30 |
| Effort required at capacity (Newton) | 221 | 304 | 343 | 457 | 314 | 343 | 381 | 392 | 392 | 392 | 392 |
| Dimensions (mm) Length = A | 138 | 164 | 198 | 198 | 164 | 198 | 228 | 367 | 367 | 410 | 598 |
| Width = B | 114 | 124 | 142 | 142 | 124 | 142 | 167 | 167 | 167 | 167 | 200 |
| Head Room = C | 271 | 360 | 453 | 453 | 490 | 570 | 690 | 720 | 720 | 820 | 1000 |
| Throat opening = D | 21.5 | 27 | 30 | 30 | 30 | 37 | 46 | 54 | 54 | 64 | 72 |
| Width = E | 51 | 55 | 67 | 67 | 86 | 102 | 112 | 160 | 260 | 152 | 302 |
| Width = F | 24 | 28 | 40 | 40 | 42 | 46 | 57 | 82 | 82 | 140 | 105 |
| Width = G | 33 | 38 | 45 | 45 | 45 | 51 | 65 | 85 | 85 | 100 | 110 |

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserves the right to modify design, dimensional parameters and component and composition of material without prior notice

