

TECHNICAL PARAMETERS

Dual speeds

Product Code	Rated Load	Lift	Lifting Motor			Cross Travel			Voltage & Fq.	I - Beam									
			Power	Rotation Speed	Lifting Speed	Power	Rotation Speed	Travelling Speed											
	(Tonnes)	(m)	(KW)	(r/min)	(m/min)	(KW)	(r/min)	(m/min)	(V & Hz)	(mm)									
KTCH005105	0.5	3	0.8 & 0.2	2880 & 720	8 & 2	0.25	1440	20	440 & 50	58-153									
KTCH010105	1	3	1.5 & 0.4	2880 & 720	8 & 2	0.4	1440	11/20	440 & 50	58-153									
Product Code	Rated Load	Unit (mm)																Diameter x Chain Fall	
		H	H1	H2	H3	A	B	D	D1	E	I	K	L	N	R	T	U		W
	(Tonnes)																		
KTCH005105	0.5	497	463	42	221	471	266	319	φ62	170	φ31	φ36	30	20	142	209	111	285	φ5x1
KTCH010105	1	563	567	20	241	569	306	340	φ95	183	φ31	φ42	35	25	169	252	111	315	φ7.1x1

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserve the right to modify design, dimensional parameters and component material without notice

