

TECHNICAL PARAMETERS

Inverter **Optional**

Product Code	Rated Load	Lift	Lifting Speed	Lifting Motor				
				Power	Rotation Speed	Phases	Voltage	Frequency
	(Tonnes)	(m)	(m/min)	(KW)	(r/min)		(V)	(Hz/s)
SCH0050105	0.5	3	6.8 & 1.7	0.75	1440 & 360	3	440	50
SCH0100105	1	3	6.6 & 1.65	1.5	1440 & 360	3	440	50
SCH0100205	1	3	3.4 & 0.85	0.75	1440 & 360	3	440	50
SCH0150105	1.5	3	8.8 & 2.2	3	1440 & 360	3	440	50
SCH0200105	2	3	6.6 & 1.65	3	1440 & 360	3	440	50

Product Code	Rated Load	Unit (mm)											Diameter x Chain Fall
		H	A	B	D	E	I	J	K	L	M	N	
	(Tonnes)												
SCH0050105	0.5	455	566	266	285	165	φ35	27	φ34	25	17	17	φ6.3x1
SCH0100105	1	520	627	302	300	176	φ42	32	φ41	32	24	24	φ7.1x1
SCH0100205	1	490	566	266	285	165	φ35	27	φ35	25	24	24	φ6.3x2
SCH0150105	1.5	640	733	343	430	265	φ48	38	φ49	40	28	28	φ10.0x1
SCH0200105	2	640	733	343	430	265	φ48	38	φ49	40	28	28	φ10.0x1

Extra Lift & higher sizes are available on request. Due to continual development of products, manufacturer reserve the right to modify design, dimensional parameters and component material without notice

Dual speeds **Optional**

