

TECHNICAL PARAMETERS

Product Code	Unit	KEPT0020-BF	KEPT0030-BF
Capacity	Q(Kg)	2000	3000
Load Center	C(mm)	600	600
Type Of Li ing		Electric	Electric
Opera ng Type		Walkie	Walkie
Material		PU	PU
Wheel Base	Y(mm)	1230/1300	1380/1450
Quan ty Of Driving/balance/bearing Wheel		1x+2/4	1x+2/4
Bearing Wheel Size	mm	Φ80x70	Φ80x70
Driving Wheel Size	mm	Φ210x75	Φ230x75
Balance Wheel Size	mm	Φ75x46	Φ75x46
Min. Fork Height	h_{13} (mm)	85	85
Max. Fork Height	mm	200	200
Max Li ing Height	h_3 (mm)	115	115
Fork Outside Width	b_5 (mm)	560/685	560/685
Fork Inside Width	b_{11} (mm)	240/365	200/325
Fork Length	l(mm)	1150/1220	1150/1220
Single Fork Size	e/s(mm)	160/50	160/50
Overall Length	L_1 (mm)	1650/1720	2055/2125
Overall Width	b_1 (mm)	685	690
Overall Height	h_{14} (mm)	1220	1215
Min Turning Radius	Wa(mm)	1385/1455	1540/1610
Travel Speed(Laden/unladen)	km/h	4/5	4/5
Li ing Speed(Laden/unladen)	mm/s	25/30	10/13
Lowering Speed (Laden/unladen)	mm/s	30/20	14/10
Fast/slow Adjustment Func on		Yes	Yes
Gradeability	%	≤4	S4/S6
Driving Mode		DC	AC
Drive Motor	Kw	24V 0.75KW	24V2.5
Li Motor	Kw	24V 0.8KW	24V0.8
Ba ery Capacity	V/Ah	2×12/80	24V/165
Charger		24V 12A	24V30A
Ba ery Weight	Kg	24	155