

OUTDOOR TERRAIN TRUCK











- Locking and Lift Machanism
- Lightweight Design Concept
- Reliable Stress, Ensure strength. Swing guide wheel is installed under the movable door seat to push the body into the carriage smoothly, which is convenient for maintenance and adjustment.

TECHNICAL PARAMETERS

Product Code	Unit	KOTT1500
Capacity	Kg	1500kg
Type of lifting		Electric
Operating type		Walkie
Wheel base	mm	1900mm
Bearing wheel size	mm	380×112mm(Solid tire)
Driving wheel siz	mm	300×90mm(Solid tire)
Min.fork height	mm	70mm
Max.fork height	mm	330mm
Max.lifting height	mm	260mm
Fork length	mm	1220mm
Single fork size	mm	100mm
Overall length	mm	2210mm
Overall width	mm	1550mm
Overall height	mm	1260mm
Min.turning radius	mm	1900mm
Travel speed(laden/unladen)	Km/hr	4/6km/h
Lifting speed(laden/unladen)	mm/sec	22/27mm/s
Lowering speed(laden/unladen)	mm/sec	65/45mm/s
Gradeability		≤4/6%
Driving mode		AC
Drive motor		1.5kw/24V
Battery capacity		24V/170Ah
Battery weight	Kg	155kg
Net weight	Kg	720 kg